

# Cisco Firepower 4100 Series Data Sheet

Enterprise Firewall

Next Generation Firewall

Next Generation IPS

Contact Us

Phone: +852-51736677

Skype: wendycisco

WhatsApp: +852-51736677

E-mail: sales@uritprice.com (Sales Inquiries)

---

# Contents

Cisco Firepower 4100 Series appliances	3
Model overview	3
Detailed performance specifications and feature highlights	3
Hardware specifications	6
Cisco Capital	9

## Cisco Firepower 4100 Series appliances

The Cisco Firepower 4100 Series is a family of seven threat-focused NGFW security platforms. Their throughput range addresses data center and internet edge use cases. They deliver superior threat defense, at faster speeds, with a smaller footprint. Cisco Firepower 4100 Series supports flow-offloading, programmatic orchestration, and the management of security services with RESTful APIs. Network Equipment Building Standards (NEBS)-compliance is supported by the Cisco Firepower 4125 platform. The 4100 Series platforms can run either the Cisco Secure Firewall ASA or Cisco Secure Firewall Threat Defense (FTD) software.

### Model overview



#### Cisco Firepower 4100 Series summary:

Model	Firewall	NGFW	IPS	Interfaces	Optional Interfaces
FPR-4110	35G	15.5G	16.5G	8 x SFP+ on-chassis	2 x NM's: 1/10/40G, FTW
FPR-4112	40G	19G	19G	8 x SFP+ on-chassis	2 x NM's: 1/10/40G, FTW
FPR-4115	80G	33G	33G	8 x SFP+ on-chassis	2 x NM's: 1/10/40G, FTW
FPR-4125	80G	45G	45G	8 x SFP+ on-chassis	2 x NM's: 1/10/40G, FTW
FPR-4145	80G	53G	55G	8 x SFP+ on-chassis	2 x NM's: 1/10/40G, FTW

### Detailed performance specifications and feature highlights

**Table 1.** Performance specifications and feature highlights for Firepower 4100 with the Cisco Secure Firewall Threat Defense (TD) image

Features	4110	4112	4115	4125	4145
<b>Throughput: FW + AVC (1024B)</b>	16.5 Gbps	19 Gbps	33 Gbps	45 Gbps	53 Gbps
<b>Throughput: FW + AVC + IPS (1024B)</b>	15.5 Gbps	19 Gbps	33 Gbps	45 Gbps	53 Gbps
<b>Maximum concurrent sessions, with AVC</b>	10 million	10 million	15 million	25 million	30 million
<b>Maximum new connections per second, with AVC</b>	64K	98K	210K	269K	365K
<b>TLS (Hardware Decryption)<sup>1</sup></b>	4.5 Gbps	4.5 Gbps	6.5 Gbps	8.5 Gbps	10 Gbps

Features	4110	4112	4115	4125	4145
<b>Throughput: NGIPS (1024B)</b>	16.5 Gbps	19 Gbps	33 Gbps	45 Gbps	55 Gbps
<b>IPSec VPN Throughput (1024B TCP w/Fastpath)</b>	8 Gbps	8.5 Gbps	12.5 Gbps	19 Gbps	24 Gbps
<b>Maximum VPN Peers</b>	10,000	10,000	15,000	20,000	20,000
<b>Multi-Instance Capable</b>	Yes				
<b>Centralized management</b>	Centralized configuration, logging, monitoring, and reporting are performed by the Management Center or alternatively in the cloud with Cisco Defense Orchestrator				
<b>Application Visibility and Control (AVC)</b>	Standard, supporting more than 4000 applications, as well as geolocations, users, and websites				
<b>AVC: OpenAppID support for custom, open source, application detectors</b>	Standard				
<b>Cisco Security Intelligence</b>	Standard, with IP, URL, and DNS threat intelligence				
<b>Cisco Secure IPS License</b>	Available; can passively detect endpoints and infrastructure for threat correlation and Indicators of Compromise (IoC) intelligence				
<b>Cisco Malware Defense for Networks</b>	Available; enables detection, blocking, tracking, analysis, and containment of targeted and persistent malware, addressing the attack continuum both during and after attacks. Integrated threat correlation with Cisco Secure Endpoint is also optionally available				
<b>Cisco Malware Analytics sandboxing</b>	Available				
<b>URL filtering: number of categories</b>	More than 80				
<b>URL filtering: number of URLs categorized</b>	More than 280 million				
<b>Automated threat feed and IPS signature updates</b>	Yes: Class-leading Collective Security Intelligence (CSI) from the Cisco Talos Group				
<b>Third-party and open-source ecosystem</b>	Open API for integrations with third-party products; Snort® and OpenAppID community resources for new and specific threats				
<b>High availability and clustering</b>	Active/active, Active/standby. Cisco Firepower 4100 Series allows clustering of up to 6 chassis				
<b>Cisco Trust Anchor Technologies</b>	Firepower 4100 Series platforms include Trust Anchor Technologies for supply chain and software image assurance				

**Note:** Performance will vary depending on features activated, and network traffic protocol mix, and packet size characteristics. Performance is subject to change with new software releases. Consult your Cisco representative for detailed sizing guidance.

<sup>1</sup> Throughput measured with 50% TLS 1.2 traffic with AES256-SHA with RSA 2048B keys.

**Table 2.** ASA Performance and capabilities on Firepower 4100 appliances

Features	4110	4112	4115	4125	4145
<b>Stateful inspection firewall throughput<sup>1</sup></b>	35 Gbps	40 Gbps	80 Gbps	80 Gbps	80 Gbps
<b>Stateful inspection firewall throughput (multiprotocol)<sup>2</sup></b>	15 Gbps	30 Gbps	40 Gbps	45 Gbps	50 Gbps
<b>Concurrent firewall connections</b>	10 million	10 million	15 million	25 million	40 million
<b>Firewall latency (UDP 64B microseconds)</b>	3.5	3.5	3.5	3.5	3.5
<b>New connections per second</b>	150,000	400,000	848K	1.1 million	1.5 million
<b>IPsec VPN throughput (450B UDP L2L test)</b>	8 Gbps	9 Gbps	15 Gbps	19 Gbps	23 Gbps
<b>Maximum VPN Peers</b>	10,000	10,000	15,000	20,000	20,000
<b>Security contexts (included; maximum)</b>	10; 250	10; 250	10; 250	10; 250	10; 250
<b>High availability</b>	Active/active and active/standby				
<b>Clustering</b>	Up to 16 appliances				
<b>Scalability</b>	VPN Load Balancing, Firewall Clustering				
<b>Centralized management</b>	Centralized configuration, logging, monitoring, and reporting are performed by Cisco Security Manager or alternatively in the cloud with Cisco Defense Orchestrator				
<b>Adaptive Security Device Manager</b>	Web-based, local management for small-scale deployments				

<sup>1</sup> Throughput measured with 1500B User Datagram Protocol (UDP) traffic measured under ideal test conditions.

<sup>2</sup> “Multiprotocol” refers to a traffic profile consisting primarily of TCP-based protocols and applications like HTTP, SMTP, FTP, IMAPv4, BitTorrent, and DNS.

<sup>3</sup> In unclustered configuration.

## Hardware specifications

**Table 3.** Cisco Firepower 4100 Series hardware specifications

Features		4110	4112	4115	4125	4145
<b>Dimensions (H x W x D)</b>		1.75 x 16.89 x 29.7 in. (4.4 x 42.9 x 75.4 cm)				
<b>Form factor (rack units)</b>		1RU				
<b>Supervisor</b>		Cisco Firepower 4000 Supervisor with 8 x 10 Gigabit Ethernet ports and 2 Network Module (NM) slots for I/O expansion				
<b>Network modules</b>		<ul style="list-style-type: none"> <li>• 8 x 10 Gigabit Ethernet Enhanced Small Form-Factor Pluggable (SFP+) network modules               <ul style="list-style-type: none"> <li>◦ 8 x 1 Gbps Fiber or 4 x 1Gbps Copper SFP Network Module</li> </ul> </li> <li>• 4 x 40 Gigabit Ethernet Quad SFP+ network modules</li> <li>• 8-port 1Gbps copper, FTW (fail to wire) Network Module               <ul style="list-style-type: none"> <li>◦ Ports that are not configured as FTW can be used as regular 1 Gb copper ports</li> </ul> </li> <li>• 6-port 1 Gbps SX Fiber FTW (fail to wire) Network Module</li> <li>• 6-port 10Gbps SR Fiber FTW (fail to wire) Network Module</li> <li>• 6-port 10Gbps LR Fiber FTW (fail to wire) Network Module</li> <li>• 2-port 40G SR FTW (fail to wire) Network Module</li> </ul>				
<b>Maximum number of interfaces</b>		Up to 24 x 10 Gigabit Ethernet (SFP+) interfaces; up to 8 x 40 Gigabit Ethernet (QSFP+) interfaces with 2 network modules; up to 24 x 1 Gigabit Ethernet ports(SFP) with network modules and fixed ports				
<b>Integrated network management ports</b>		1 Gigabit Ethernet Supports 1-G fiber or copper SFPs				
<b>Serial port</b>		1 x RJ-45 console				
<b>USB</b>		1 x USB 2.0				
<b>Storage</b>		200 GB	400 GB	400 GB	800 GB	800 GB
<b>Power supplies</b>	Configuration	Single 1100W AC, dual optional. Single/dual 950W DC optional <sup>1,2</sup>	Single 1100W AC, dual optional. Single/dual 950W DC optional <sup>1,2</sup>	Single 1100W AC, dual optional. Single/dual 950W DC optional <sup>1,2</sup>	Dual 1100W AC <sup>1</sup>	Dual 1100W AC <sup>1</sup>
	AC input voltage	100 to 240V AC				
	AC maximum input current	13A				
	AC maximum output power	1100W				
	AC frequency	50 to 60 Hz				
	AC efficiency	>92% at 50% load				

Features		4110	4112	4115	4125	4145
	DC input voltage	-40V to -60VDC				
	DC maximum input current	27A				
	DC maximum output power	950W				
	DC efficiency	>92.5% at 50% load				
	Redundancy	1+1				
<b>Fans</b>		6 hot-swappable fans				
<b>Noise</b>		Typical 63 dBA, max is 74 dBA				
<b>Rack mountable</b>		Yes, mount rails included (4-post EIA-310-D rack)				
<b>Weight</b>		4110: 36 lb (16 kg): 2 x power supplies, 2 x NMs, 6 x fans; 30 lb (13.6 kg): no power supplies, no NMs, no fans 4112/4115/4125/4145: 39.4 lb (17.87 kg) 2 x power supplies, 2 x NMs, 6 x fans; 31.4 lb (14.24 kg) no power supplies, no NMs, no fans				
<b>Temperature: operating</b>		32 to 104°F (0 to 40°C)	32 to 104°F (0 to 40°C)	32 to 104°F (0 to 40°C)	32 to 104°F (0 to 40°C) or NEBS operation (see below)	32 to 104°F (0 to 40°C), at sea level
<b>Temperature: nonoperating</b>		-40 to 149°F (-40 to 65°C)				
<b>Humidity: operating</b>		5 to 95% noncondensing				
<b>Humidity: nonoperating</b>		5 to 95% noncondensing				
<b>Altitude: operating</b>		10,000 ft (max)	10,000 ft (max)	10,000 ft (max)	10,000 ft (max)	10,000 ft (max)
<b>Altitude: nonoperating</b>		40,000 ft (max)				
<b>NEBS operation (FPR 4125 only)</b>		Operating altitude: 0 to 13,000 ft (3960 m) Operating temperature: Long term: 0 to 45°C, up to 6,000 ft (1829 m) Long term: 0 to 35°C, 6,000 to 13,000 ft (1829 to 3964 m) Short term: -5 to 50°C, up to 6,000 ft (1829 m)				

<sup>1</sup> Dual power supplies are hot-swappable.

**Table 4.** Cisco Firepower 4100 Series NEBS, Regulatory, Safety, and EMC Compliance

Specification	Description
<b>Regulatory compliance</b>	Products comply with CE markings per directives 2004/108/EC and 2006/108/EC
<b>Safety</b>	<ul style="list-style-type: none"> <li>• UL 60950-1</li> <li>• CAN/CSA-C22.2 No. 60950-1</li> <li>• EN 60950-1</li> <li>• IEC 60950-1</li> <li>• AS/NZS 60950-1</li> <li>• GB4943</li> </ul>
<b>EMC: Emissions</b>	<ul style="list-style-type: none"> <li>• 47CFR Part 15 (CFR 47) Class A (FCC Class A)</li> <li>• AS/NZS CISPR22 Class A</li> <li>• CISPR22 CLASS A</li> <li>• EN55022 Class A</li> <li>• ICES003 Class A</li> <li>• VCCI Class A</li> <li>• EN61000-3-2</li> <li>• EN61000-3-3</li> <li>• KN22 Class A</li> <li>• CNS13438 Class A</li> <li>• EN300386</li> <li>• TCVN7189</li> </ul>
<b>EMC: Immunity</b>	<ul style="list-style-type: none"> <li>• EN55024</li> <li>• CISPR24</li> <li>• EN300386</li> <li>• KN24</li> <li>• TVCN 7317</li> <li>• EN-61000-4-2, EN-61000-4-3, EN-61000-4-4, EN-61000-4-5, EN-61000-4-6, EN-61000-4-8, EN61000-4-11</li> </ul>



---

## Cisco Capital

### Flexible payment solutions to help you achieve your objectives

Cisco Capital makes it easier to get the right technology to achieve your objectives, enable business transformation and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services and complementary third-party equipment in easy, predictable payments.

[Learn more.](#)

### Contact Us

Phone: +852-51736677

Skype: wendycisco

WhatsApp: +852-51736677

E-mail: [sales@uritprice.com](mailto:sales@uritprice.com) (Sales Inquiries)

**Americas Headquarters**  
Cisco Systems, Inc.  
San Jose, CA

**Asia Pacific Headquarters**  
Cisco Systems (USA) Pte. Ltd.  
Singapore

**Europe Headquarters**  
Cisco Systems International BV Amsterdam,  
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at <https://www.cisco.com/go/offices>.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <https://www.cisco.com/go/trademarks>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)