IIIIII CISCO The bridge to possible



Cisco IP Phone 8841 Data Sheet

Contact Us Phone: +852-51736677 Skype: wendycisco WhatsAPP: +852-51736677

E-mail: sales@uritprice.com (Sales Inquiries)

Website: https://www.uritprice.com

Contents

Features and benefits	4
Licensing	5
Product sustainability	6
Product specifications	6
Ordering information	10
Warranty	11
CSR/Social Responsibility	11
Cisco unified communications services	11
Cisco Capital	11
More information	12

The Cisco[®] IP Phone 8841 is a business-class collaboration endpoint that delivers highfidelity, reliable, secure, and scalable voice communication for small to large enterprise businesses.



With the Cisco IP Phone 8841, you can increase personal productivity through an engaging user experience that is both powerful and easy-to-use. The IP Phone 8841 combines an attractive new ergonomic design with wideband audio for crystal clear voice communications, "always-on" reliability, encrypted voice communications to enhance security, and access to a comprehensive suite of unified communication features from Cisco on-premises and hosted infrastructure platforms and third party hosted call control.

The Cisco IP Phone 8841 offers five programmable line keys. You can configure keys to support either multiple directory numbers or call features such as speed dial. You can also boost productivity by handling multiple calls for each directory number, using the multicall-per-line feature. Fixed function keys give you one-touch access to applications, messaging, directory, as well as often-used calling features such as hold/resume, transfer, and conference. Backlit acoustic keys provide flexibility for audio path selection and switching.

Additionally, Cisco has adopted circular design principles in its products by pioneering the use of postconsumer recycled plastic. The 8841 is one of the models that now reduces the use of natural resources while closing the loop with its own electronic waste. Learn more about what this means by visiting the <u>Cisco's Circular Economy website</u>.

Other key features of the phone follow:

- The Cisco IP Phone 8841 offers a 5-in. high-resolution (800 x 480) widescreen VGA backlit color display. Localized language support, including right-to-left on-screen text, meets the needs of global users.
- The phone supports a built-in Gigabit Ethernet switch for your PC connection.
- Support for Cisco EnergyWise[™] technology makes the Cisco IP Phone 8841 more energy-efficient and ecofriendly; the phone is qualified by Energy Star organization.
- An optional wall-mount kit is orderable as a spare part for customers seeking this capability.

Features and benefits

Table 1 lists features and benefits of the Cisco IP Phone 8841.

Table 1.Features and Benefits

Features	Benefits
Hardware Features	
Ergonomic design	• The phone offers an easy-to-use interface and provides a traditional telephony-like user experience.
Graphical display	• The 800 × 480, 24-bit color, 5-in. WVGA display provides scrollable access to calling features and text-based XML applications.
Handset	 The handset is a standard wideband-capable audio handset (connects through an RJ-9 port). The standard coiled cord has a custom end for concealed cable routing beneath the phone (cord length is approximately 21 in. [55 cm] coiled and up to 72 in. (183 cm) extended). The handset is Hearing Aid-Compatible (HAC) and meets Federal Communications Commission (FCC) loudness requirements for the Americans with Disabilities Act (ADA). Section 508 loudness requirements can be achieved using industry-standard inline handset amplifiers such as Walker Equipment W-10 or CE-100 amplifiers. The dial pad is also ADA-compliant.
Speaker phone	 A full-duplex speakerphone gives you flexibility in placing and receiving calls with hands free. For added security, the audible Dual Tone Multifrequency (DTMF) tones are masked when the speakerphone mode is used.
Analog headset	• The analog headset jack is a standard wideband-capable RJ-9 audio port.
AUX port	• You can use an auxiliary port to support electronic hookswitch control with a third-party headset connected to it.
Ethernet switch	 An internal 2-port Cisco Ethernet switch allows for a direct connection to a 10/100/1000BASE-T Ethernet network (IEEE 802.3i/802.3u/802.3ab) through a RJ-45 interface with single LAN connectivity for both the phone and a co-located PC. The system administrator can designate separate VLANs (IEEE 802.1Q) for the PC and phone, providing improved security and reliability of voice and data traffic.
Keys	 The phone has the following keys: Line keys Soft keys Back and release keys Four-way navigation and select keys Hold/Resume, Transfer, and Conference keys Messaging, Application, and Directory keys Standard keypad Volume-control toggle key Speakerphone, headset, and mute keys
Backlit indicator	• The phone supports backlit indicators for the audio path keys (handset, headset, and speakerphone), select key, line keys, and message waiting.
Replaceable bezel	• The phone includes a black bezel; an optional silver bezel is also orderable separately.

Features	Benefits
Dual-position foot stand	 The display is easy-to-view and the buttons and keys are easy-to-use. The two-position foot stand supports viewing angles of 35 and 50 degrees; you can remove the foot stand for wall mounting, with mounting holes located on the base of the phone.
Wall-mountable	• You can install the phone on a wall using an optional wall-mount kit (orderable separately).
Physical security	• The phone is compatible with the Kensington Security Slot (K-Slot) antitheft system.
Power Features	
IEEE Power over Ethernet (PoE)	• IEEE Power over Ethernet class 2. The phone is compatible with both IEEE 802.3af and 802.3at switch blades and supports both Cisco Discovery Protocol and Link Layer Discovery Protocol – Power over Ethernet (LLDP-PoE).
Cisco IP Phone Power Cube 4	• This optional power cube is used as an AC-to-DC (48V) power supply for non-PoE deployments. Use of the power cube 4 also requires the use of one of the corresponding AC country cords.
Call-Control Support	
Cisco Unified Communications Manager	 8.5.1 (Non-secured mode Only) 8.6.2 9.1.2 10.5.2 11.0 and later
Cisco Unified Communications Manager Express (Unified CME)	• 10.0 and later through fast track
Cisco Business Edition 6000 (BE 6000)	 8.6.2 9.1.2 10.5.2 11.0 and later
Cisco Hosted Collaboration Solution (HCS)	• 8.6.2 and later (using supported UCM versions above)

Licensing

The Cisco IP Phone 8841 requires an Enhanced User Connect License (UCL) in order to connect to Cisco Unified Communications Manager.

Product sustainability

Refer to the <u>CSR/Social Responsibility section</u> for more information on Cisco's environmental sustainability policies and initiatives.

Sustainability Topic		Reference
General	Information on product-material-content laws and regulations	<u>Materials</u>
	Information on electronic waste laws and regulations, including our products, batteries and packaging	WEEE Compliance
	Certification and compliance	Table 2. Features and specifications of Cisco IP Phone 8861
	Information on product takeback and resuse program	Cisco Takeback and Reuse Program
Power	Cisco EnergyWise	Key Features
	Power Features	Table 1. Features and benefits
Material		
	Physical dimensions and Weight	Table 2. Features and specifications of Cisco IP Phone 8861
	Post-consumer recycled plastic	Circular design principles

Product specifications

Table 2 lists the features and specifications of the Cisco IP Phone 8841.

Table 2.Features and Specifications

Features	Specifications
Audio	 Automatic Gain Control Comfort Noise Generation Silence Suppression/Voice Activity Detection Acoustic Echo Cancellation (AEC) Dynamic Noise Reduction
Audio codec support	 G.711a-law and mu-law, G.722, G.729a/b, Internet Low Bitrate Codec (iLBC), and Internet Speech Audio Codec (iSAC), G.722.1, G.772.2, OPUS
Call features	 + Dialing Abbreviated dialing Adjustable ring tones and volume levels Adjustable display brightness Agent greeting

Features	Specifications
	Auto-answer
	Auto-detection of headset
	• cBarge
	• Busy Lamp Field (BLF)
	Busy Lamp Field (BLF) Pickup
	Busy Lamp Field (BLF) speed dial
	Callback
	Call forward
	Call forward notification
	Call filter
	Call history lists
	Call park
	Call pickup
	Call timer
	Call waiting
	Call chaperone
	Caller ID
	Corporate directory
	Conference, including traditional Join feature
	Cross Cluster Extension Mobility (EMCC)
	Direct transfer
	• Extension mobility
	Fast-dial service
	Forced access codes and client matter codes
	Group call pickup
	Hold
	Intercom
	Immediate divert
	Malicious-caller ID
	Message-Waiting Indicator (MWI)
	 Meet-me conference Mobility
	Music on Hold (MoH)
	Mute Network profiles (outemptic)
	 Network profiles (automatic) On- and off-network distinctive ringing
	Personal directory
	Personal directory PickUp
	Predialing before sending
	Privacy
	 Privacy Private Line Automated Ringdown (PLAR)
	Redial
	Redial Ring tone per line appearance
	Service Uniform Resource Locator (URL)
	Shared line

Features	Specifications
	Silent monitoring and recording
	Speed dial
	Time and date display
	• Transfer
	Uniform Resource Identifier (URI) dialing
	Visual voice mail
	Voice mail
	Whisper coaching
Electronic hookswitch	• You can control the hookswitch electronically with a third-party headset connected to the auxiliary port.
Quality-of-Service (QoS) options	• The phone supports Cisco Discovery Protocol and 802.1Q/p standards, and can be configured with an 801.1Q VLAN header containing the VLAN ID overrides configured by the Admin VLAN ID.
Network features	Session Initiation Protocol (SIP) for signaling
	Session Description Protocol (SDP)
	IPv4 and IPv6
	• User Datagram Protocol (UDP) (used only for Real-Time Transport Protocol [RTP] streams)
	Dynamic Host Configuration Protocol (DHCP) client or static configuration
	Gratuitous Address Resolution Protocol (GARP)
	Domain Name System (DNS)
	Trivial File Transfer Protocol (TFTP)
	Secure Hypertext Transfer Protocol (HTTPS)
	• VLAN
	Real-Time Transport Protocol (RTP)
	Real-Time Control Protocol (RTCP)
	Cisco Peer-to-Peer Distribution Protocol (PPDP)
	Cisco Discovery Protocol
	LLDP (including LLDP-MED)
	Switch speed auto-negotiation
Security features	Secure boot
	Secure credential storage
	Device authentication
	Configuration file authentication and encryption
	Image authentication
	Random bit generation
	Hardware cryptographic acceleration
	Certificate Authority Proxy Function (CAPF)
	Manufacturer-Installed Certificates (MIC)
	Locally Significant Certificates (LSC)
	 Ethernet 802.1x supplicant options: Extensible Authentication Protocol-Flexible Authentication via Secure Tunneling (EAP-FAST) and Extensible Authentication Protocol-Transport Layer Security (EAP-TLS)
	Signaling authentication and encryption using TLS
	Media authentication and encryption using SRTP
	HTTPS for client and server
	Secure Shell (SSH) Protocol server
	SSL-based VPN client

Features	Specifications
Physical dimensions (H × W × D)	 9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm) (excluding foot stand)
Weight (with handset)	• 2.58 lb (1.17 kg)
Phone-casing composition	Polycarbonate acrylonitrile butadiene styrene (ABS) textured plastic; Cosmetic class A
Operational temperature	• 32 to 104°F (0 to 40°C)
Nonoperational temperature shock	• 14 to 140°F (-10 to 60°C)
Humidity	Operating 10 to 90%, noncondensingNonoperating 10 to 95%, noncondensing
Language support	 Arabic (Arabic Area) Bulgarian (Bulgaria) Catalan (Spain) Chinese (China) Chinese (Taiwan) Croatian (Croatia) Czech (Czech Republic) Danish (Denmark) Dutch (Netherlands) English (United Kingdom) Estonian (Estonia) French (France) French (Canada) Finnish (Finland) German (Germany) Greece) Hebrew (Israel) Lutivanian (Hungary) Italian (Italy) Japanese (Japan) Lativian (Latvia) Korean (Korea Republic) Norwegian (Norway) Politsh (Poland) Portuguese (Brazil) Romanian (Romania) Russian (Russian Federation) Spanish (Columbia) Spanish (Columbia)

Features	Specifications
	Slovak (Slovakia)
	Swedish (Sweden)
	Serbian (Republic of Serbia)
	Serbian (Republic of Montenegro)
	Slovenian (Slovenia)
	• Thai (Thailand)
	• Turkish (Turkey)

Ordering information

Table 3 gives ordering information for the phone and its accessories.

Table 3.Ordering information

Product Number	Description
CP-8841-K9=	Cisco IP Phone 8841, Charcoal
СР-8841-W-К9=	Cisco IP Phone 8841, White
CP-DX-HS=	Spare Handset for Cisco 7800, 8800, DX600 Series, Charcoal
CP-DX-CORD=	Spare Handset Cord for Cisco 8800, DX600 Series, Charcoal
CP-DX-W-HS=	Spare Handset for Cisco IP Phone 7800, 8800, DX600 Series, White
CP-DX-W-CORD=	Spare Handset Cord for Cisco IP Phone 8800, DX600 Series, White
CP-8800-WMK=	Spare Wallmount Kit for Cisco IP Phone 8800 Series
CP-8800-FS=	Spare Foot stand for Cisco IP Phone 8800 Series
CP-8800-B-BEZEL=	Spare Black Bezel for Cisco IP Phone 8800 Series
CP-8800-S-BEZEL=	Spare Silver Bezel for Cisco IP Phone 8800 Series
CP-PWR-CUBE-4	Cisco Power Cube 4
CP-PWR-CORD-AP=	Power Cord Asia Pacific
CP-PWR-CORD-AR=	Power Cord Argentina
CP-PWR-CORD-AU=	Power Cord Australia
CP-PWR-CORD-BZ=	Power cord for Brazil
CP-PWR-CORD-CE=	Power Cord European
CP-PWR-CORD-CN=	Power Cord China
CP-PWR-CORD-JP=	Power Cord Japan
CP-PWR-CORD-NA=	Power Cord North America

Product Number	Description
CP-PWR-CORD-SW=	Power Cord Switzerland
CP-PWR-CORD-UK=	Power Cord United Kingdom

Warranty

The Cisco IP Phone 8841 phones are covered by a Cisco standard 1-year replacement warranty.

CSR/Social Responsibility

Information about Cisco's Environmental, Social and Governance (ESG) policies and initiatives can be found in Cisco's <u>Corporate Social Responsibility</u> (CSR) Report.

Cisco unified communications services

Cisco and our certified partners can help you set up a secure, dependable Cisco Unified Communications Solution, meeting aggressive deployment schedules and accelerating business advantage. Cisco's portfolio of services is based on proven methodologies for unifying voice, video, data, and mobile applications on fixed and mobile networks.

Our unique lifecycle approach to services defines what's needed at each phase of the solution lifecycle. Customized planning and design services help you create a solution that meets your business needs. Awardwinning technical support helps you boost your operational efficiency. Remote management services simplify day-to-day operations. And optimization services let you modify and improve your network solution when business needs change.

Cisco Capital

Flexible payment solutions to help you achieve your objectives

Cisco Capital makes it easier to get the right technology to achieve your objectives, enable business transformation and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services and complementary third-party equipment in easy, predictable payments. Learn more.

Contact Us

Phone: +852-51736677

Skype: wendycisco

WhatsAPP: +852-51736677

E-mail: sales@uritprice.com (Sales Inquiries)

Website: https://www.uritprice.com

Americas Headquarters Cisco Systems, Inc.

San Jose, CA

Asia Pacific Headquarters Cisco Systems (USA) Pte. Ltd. Singapore Europe Headquarters Cisco Systems International BV Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at https://www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: https://www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Printed in USA

C78-731638-09

12/21