



Cisco IP Phone 8845 Data Sheet

Contact Us

Phone: +852-51736677

Skype: wendycisco

WhatsAPP: +852-51736677

E-mail: sales@uritprice.com (Sales

Inquiries)

Website: https://www.uritprice.com

Contents

Features and benefits	4
Licensing	6
Product specifications	6
Ordering information	11
Warranty	12
Cisco Unified Communications Services	12
Cisco Capital	12
More information	12

https://www.uritprice.com



Do you need high-fidelity and reliable voice communications? Secure and scalable communications? An entry to HD video? The business-class Cisco® IP Phone 8845 can deliver all this and more.

The Cisco IP Phone 8845 can help you increase personal productivity through powerful and easy-to-use user experiences. It combines an attractive new ergonomic design with 720p HD video and wideband audio for crystal-clear video and voice communications and "always-on" reliability. The 8845 encrypts video and voice communications for security, and offers access to a comprehensive suite of unified communications features.

In addition, Cisco Intelligent Proximity brings the worlds of desk and mobile together for you when you are using your mobile device at the desk for your work. You can move the audio path over to the 8845 during active mobile calls to take advantage of its superior audio acoustics. An example would be to share a conversation with a colleague who listens in. This capability gives you greater flexibility when at your desk.

The Cisco IP Phone 8845 offers five programmable line keys. You can configure keys to support either multiple directory numbers or call features such as speed dial. You can also boost productivity by handling multiple calls for each directory number, using the multicall-per-line feature. Fixed function keys give you one-touch access to applications, messaging, directory, as well as often-used calling features such as hold/resume, transfer, and conference. Backlit acoustic keys provide flexibility for audio path selection and switching.

Other key features of the phone follow:

- The Cisco IP Phone 8845 offers a 5-in. high-resolution (800 x 480) widescreen VGA backlit color display. Localized language support, including right-to-left on-screen text, meets the needs of global users.
- 720p HD two-way video (encode and decode).
- The phone supports a built-in Gigabit Ethernet switch for your PC connection.
- An optional wall-mount kit is orderable as a spare part for customers who want this capability.

Features and benefits

Table 1 lists features and benefits of the IP Phone 8845.

Table 1. Features and benefits

Features	Benefits
Hardware Features	
Ergonomic design	The phone offers an easy-to-use interface and provides a traditional telephony-like user experience
Graphical display	• The 800 × 480, 24-bit color, 5-in. WVGA display provides scrollable access to calling features and text-based XML applications
Audio	 Automatic Gain Control Comfort Noise Generation Silence Suppression/Voice Activity Detection Acoustic Echo Cancellation (AEC) Dynamic Noise Reduction
Audio codec support	G.711 a-law and mu-law, G.722, G.729a/b, Internet Low Bitrate Codec (iLBC), and Internet Speech Audio Codec (iSAC), G.722.1, G.772.2, OPUS
Video	720p HD video (encode and decode)H.264/AVC
Handset	 The handset is a standard wideband-capable audio handset (connects through an RJ-9 port) The standard coiled cord has a custom end for concealed cable routing beneath the phone (cord length is approximately 21 in. [55 cm] coiled and up to 72 in. (183 cm) extended) The handset is Hearing Aid-Compatible (HAC) and meets Federal Communications Commission (FCC) loudness requirements for the Americans with Disabilities Act (ADA). You can achieve Section 508 loudness requirements with industry-standard inline handset amplifiers such as Walker Equipment W-10 or CE-100 amplifiers. The dial pad is also ADA-compliant
Speaker phone	 A full-duplex speakerphone gives you flexibility in placing and receiving calls with hands free. For added security, the Audible Dual Tone Multifrequency (DTMF) tones are masked when the speakerphone mode is used.
Analog headset	The analog headset jack is a standard wideband-capable RJ-9 audio port
AUX port	You can use an auxiliary port to support electronic hookswitch control with a third-party headset connected to it
Ethernet switch	 An internal 2-port Cisco Ethernet switch allows for a direct connection to a 10/100/1000BASE-T Ethernet network (IEEE 802.3i/802.3u/802.3ab) through an RJ-45 interface with single LAN connectivity for both the phone and a co-located PC The system administrator can designate separate VLANs (IEEE 802.1Q) for the PC and phone, providing improved security and reliability of voice and data traffic
Bluetooth	 Bluetooth 4.1 LE, Enhanced Data Rate (EDR) Class 1 technology (up to 66-ft [20m] range) is supported Hands-Free Profile (HFP) is supported for untethered headset connections and voice communications Phone Book Access Profile (PBAP) is supported for phone book object exchange between devices

Features	Benefits
Keys	 The phone has the following keys: Line keys Soft keys Back and release keys Four-way navigation and select keys Hold/Resume, Transfer, and Conference keys Messaging, Application, and Directory keys Standard keypad Volume-control toggle key Speakerphone, headset, and mute keys
Backlit indicator	 The phone supports backlit indicators for the audio path keys (Handset, Headset, and Speakerphone), select key, line keys, and message waiting
Replaceable bezel	The phone includes a black bezel; an optional silver bezel is also orderable separately
Dual-position foot stand	• The display is easy-to-view and the buttons and keys are easy-to-use. The two-position foot stand supports viewing angles of 35 and 50 degrees; you can remove the foot stand for wall mounting, with mounting holes located on the base of the phone
Wall-mountable	You can install the phone on a wall using an optional wall-mount kit (orderable separately)
Physical security	The phone is compatible with the Kensington Security Slot (K-Slot) antitheft system
Power Features	
IEEE Power over Ethernet (PoE)	 PoE on the phone is IEEE Power over Ethernet class 2. The phone is compatible with both IEEE 802.3af and 802.3at switch blades and supports both Cisco Discovery Protocol and Link Layer Discovery Protocol - Power over Ethernet (LLDP-PoE)
Cisco IP Phone Power Cube 4	• This optional power cube is used as an AC-to-DC (48V) power supply for non-PoE deployments. Use of the power cube 4 also requires the use of one of the corresponding AC country cords
Call-Control Support	
Cisco Unified Communications Manager	 8.5.1 (non-secured mode only) 8.6.2 9.1.2 10.5.2 11.0 and later
Cisco Unified Communications Manager Express (Unified CME)	Planned to be supported 11.5
Cisco Business Edition 6000 (BE 6000)	8.6.29.1.210.5.211.0 and later
Cisco Hosted Collaboration Solution (HCS)	8.6.2 and later (using supported UCM versions listed previously)

Licensing

The IP Phone 8845 requires an Enhanced User Connect License (UCL) in order to connect to Cisco Unified Communications Manager.

Product specifications

Table 2 lists the features and specifications of the 8845.

Table 2. Features and specifications

Features	Specifications
Audio codec support	G.711a-law and mu-law, G.722, G.729a, Internet Low Bitrate Codec (iLBC), and Internet Speech Audio Codec (iSAC)
Call features	• + Dialing
	Abbreviated dialing
	Adjustable ring tones and volume levels
	Adjustable display brightness
	Agent greeting
	Application launch pad
	Auto-answer
	Auto-detection of headset
	• cBarge
	Busy Lamp Field (BLF)
	BLF Pickup
	BLF speed dial
	Callback
	Call forward
	Call forward notification
	Call filter
	Call history lists
	Call park
	Call pickup
	Call timer
	Call waiting
	Call chaperone
	Caller ID
	Corporate directory
	Conference, including traditional Join feature
	Cross-Cluster Extension Mobility (EMCC)
	Direct transfer
	Extension mobility
	Fast-dial service
	Forced access codes and client matter codes
	Group call pickup
	• Hold
	• Intercom
	Immediate divert

Features	Specifications
	Malicious-caller ID Message-Waiting Indicator (MWI) Meet-me conference Mobility Music on Hold (MoH) Mute Network profiles (automatic) On- and off-network distinctive ringing Personal directory PickUp Predialing before sending Privacy Private Line Automated Ringdown (PLAR) Redial Ring tone per line appearance Service Uniform Resource Locator (URL) Shared line Silent monitoring and recording Speed dial Time and date display Transfer Uniform Resource Identifier (URI) dialing Visual Voicemail
Mobility and remote access	You can deploy the phones remotely with the following two options: • You can have your phone remotely registered to the on-premises network through a built-in VPN client if the administrator has provisioned this VPN feature • You also can directly connect to the on-premises network without VPN through Cisco Expressway if you are provided with log-in credentials. Contact your system administrator
Electronic hookswitch	You can control the hookswitch electronically with a third-party headset connected to the auxiliary port.
Cisco Intelligent Proximity	 Audio path moving sends audio through the IP Phone 8861 for a mobile device-connected call Call-history synchronization allows you to view placed and missed calls of your mobile device from the IP Phone 8845 Contact synchronization allows you to synchronize the contact objects from your mobile device to your 8845
Quality-of-Service (QoS) options	 The phone supports Cisco Discovery Protocol and 802.1Q/p standards, and you can configure it with an 801.1Q VLAN header containing the VLAN ID overrides configured by the Admin VLAN ID

Features	Specifications
Network features	 Session Initiation Protocol (SIP) for signaling Session Description Protocol (SDP) IPv4 and IPv6 User Datagram Protocol (UDP) (used only for Real-Time Transport Protocol [RTP] streams) Dynamic Host Configuration Protocol (DHCP) client or static configuration Gratuitous Address Resolution Protocol (GARP) Domain Name System (DNS) Trivial File Transfer Protocol (TFTP) Secure HTTP (HTTPS) VLAN Real-Time Transport Protocol (RTCP) Real-Time Control Protocol (RTCP) Cisco Peer-to-Peer Distribution Protocol (PPDP) Cisco Discovery Protocol LLDP (including LLDP Media Endpoint Discovery [LLDP-MED]) Switch speed auto-negotiation
Security features	 Secure boot Secure credential storage Device authentication Configuration file authentication and encryption Image authentication Random bit generation Hardware cryptographic acceleration Certificate Authority Proxy Function (CAPF) Manufacturer-Installed Certificates (MIC) Locally Significant Certificates (LSC) Ethernet 802.1x supplicant options: Extensible Authentication Protocol-Flexible Authentication via Secure Tunneling (EAP-FAST) and Extensible Authentication Protocol-Transport Layer Security (EAP-TLS) Signaling authentication and encryption using TLS Media authentication and encryption using SRTP HTTPS for client and server Secure Shell (SSH) Protocol server SSL-based VPN client
Physical dimensions (H × W × D)	• 9.01 x 10.13 x 3.87 in. (228.78 x 257.34 x 98.39 mm) (excluding foot stand)
Weight (with handset)	• 2.97 lb (1.35 kg)
Phone-casing composition	Polycarbonate acrylonitrile butadiene styrene (ABS) textured plastic; Cosmetic class A
Operating temperature	• 32 to 104°F (0 to 40°C)
Nonoperating temperature shock	• 14 to 140°F (-10 to 60°C)
Humidity	Operating 10 to 90%, noncondensingNonoperating 10 to 95%, noncondensing

Features	Specifications
Language support	Arabic (Arabic Area)
	Bulgarian (Bulgaria)
	Catalan (Spain)
	Chinese (China)
	Chinese (Hong Kong)
	Chinese (Taiwan)
	Croatian (Croatia)
	Czech (Czech Republic)
	Danish (Denmark)
	• Dutch (Netherlands)
	English (United Kingdom)
	• Estonian (Estonia)
	• French (France)
	• French (Canada)
	• Finnish (Finland)
	German (Germany)
	• Greek (Greece)
	Hebrew (Israel)
	Hungarian (Hungary)
	• Italian (Italy)
	• Japanese (Japan)
	• Latvian (Latvia)
	Lithuanian (Lithuania)
	Korean (Korea Republic)
	Norwegian (Norway)
	• Polish (Poland)
	Portuguese (Portugal)
	Portuguese (Brazil)
	Romanian (Romania)
	Russian (Russian Federation)
	Spanish (Columbia)
	• Spanish (Spain)
	Slovak (Slovakia)
	Swedish (Sweden)
	Serbian (Republic of Serbia)
	Serbian (Republic of Montenegro)
	Slovenian (Slovenia)
	• Thai (Thailand)
	• Turkish (Turkey)

https://www.uritprice.com

Specifications Features • Regulatory compliance **Certification and** compliance CE Markings per directives 2004/108/EC and 2006/95/EC Safety UL 60950 Second Edition CAN/CSA-C22.2 No. 60950 Second Edition EN 60950 Second Edition (including A11 and A12) IEC 60950 Second Edition (including A11 and A12) AS/NZS 60950 · GB4943 • EMC - Emissions 47CFR Part 15 (CFR 47) Class B • AS/NZS CISPR22 Class B OISPR22: 2005 w/Amendment 1: 2005 Class B EN55022: 2006 w/Amendment 1: 2007 Class B • ICES003 Class B VCCI Class B · EN61000-3-2 EN61000-3-3 KN22 Class B • EMC - Immunity · EN55024 CISPR24 · EN60601-1-2 。 KN24 Armadillo Light Telecom FCC Part 68 HAC · CS-03-HAC AS/ACIF S004 AS/ACIF S040 NZ PTC 220 Industry standards: TIA 810 and TIA 920 Industry standards: IEEE 802.3 Ethernet and IEEE 802.3af and 802.3at Korea (RRA Public Notification 2010-36, Nov. 1, 2010) Korea (RRA Announce 2011-2, Feb. 28, 2011) Radio • FCC Part 2.1093 (BT RF Exposure TR) RSS-102 (BT RF Exposure TR) ∘ RSS-210 EN 300.328 EN50385 (BT RF Exposure TR) EN 301-489-1 o EN 301-489-17 NCC LP0002 Korea (RRL No. 2006-128, RRL No. 2006-129) • Japan Bluetooth GFSK/EDR

Ordering information

Table 3 gives ordering information for the phone and its accessories.

 Table 3.
 Ordering information

Product Number	Description
CP-8845-K9=	Cisco IP Phone 8845, Charcoal
CP-8845-W-K9=	Cisco IP Phone 8845, White
CP-DX-HS=	Spare Handset for Cisco 7800, 8800, DX600 Series, Charcoal
CP-DX-CORD=	Spare Handset Cord for Cisco 8800, DX600 Series, Charcoal
CP-8800-VIDEO-WMK=	Spare Wallmount Kit for Cisco IP Phone 8800 Video Series
CP-8800-FS=	Spare Foot stand for Cisco IP Phone 8800 Series
CP-8800-B-VID-BEZEL=	Spare Black Bezel for Cisco IP Phone 8800 Video Series
CP-8800-S-VID-BEZEL=	Spare Silver Bezel for Cisco IP Phone 8800 Video Series
CP-PWR-CUBE-4	Cisco Power Cube 4
CP-PWR-CORD-AP=	Power Cord Asia Pacific
CP-PWR-CORD-AR=	Power Cord Argentina
CP-PWR-CORD-AU=	Power Cord Australia
CP-PWR-CORD-BZ=	Power cord for Brazil
CP-PWR-CORD-CE=	Power Cord European
CP-PWR-CORD-CN=	Power Cord China
CP-PWR-CORD-JP=	Power Cord Japan
CP-PWR-CORD-NA=	Power Cord North America
CP-PWR-CORD-SW=	Power Cord Switzerland
CP-PWR-CORD-UK=	Power Cord United Kingdom

Warranty

The Cisco IP Phone 8845 phones are covered by a Cisco standard 1-year replacement warranty.

Cisco Unified Communications Services

Cisco and our certified partners can help you set up a secure, dependable Cisco Unified Communications Solution, meeting aggressive deployment schedules and accelerating business advantage. Our portfolio of services is based on proven methodologies for unifying voice, video, data, and mobile applications on fixed and mobile networks.

Our unique lifecycle approach to services defines what's needed at each phase of the solution lifecycle. Customized planning and design services help you create a solution that meets your business needs. Award winning technical support helps you boost your operational efficiency. Remote management services simplify day-to-day operations. And optimization services let you modify and improve your network solution when business needs change.

Cisco Capital

Flexible payment solutions to help you achieve your objectives

Cisco Capital makes it easier to get the right technology to achieve your objectives, enable business transformation and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services and complementary third-party equipment in easy, predictable payments. Learn more.

Contact Us

Phone: +852-51736677

-Skype: wendycisco

WhatsAPP: +852-51736677

E-mail: sales@uritprice.com (Sales Inquiries)

Website: https://www.uritprice.com

Americas Headquarters Cisco Systems, Inc. San Jose, CA Asia Pacific Headquarters Cisco Systems (USA) Pte. Ltd. Singapore

Europe HeadquartersCisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at https://www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: https://www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Printed in USA C78-734730-06 12/21

https://www.uritprice.com